

Industrial Batteries / Network Power

Sprinter P / XP



*»Reliable power for
increased security«*



Industrial Batteries

The powerful range of Network Power

GNB® Industrial Power offers reliable energy storage solutions for critical systems requiring uninterrupted power supply. With a comprehensive product range based on state-of-the-art technologies, GNB delivers the right battery for every application.

The below table is only indicative and depends on the specific customer application. For more information please ask a GNB sales representative.

| Applications | Battery ranges | | | | | | | | | | | | | | | | | | |
|--------------------|----------------|---------|------|------|-------|------|-------------|----------|------|----------|-------|----------|-----------|---------|------|------|-----------------|-------|------|
| | Sonnenschein | | | | | | | Marathon | | Sprinter | | Absolyte | Powerfit | Classic | | | | | |
| | A400/A600 | A400 FT | A500 | A700 | SOLAR | RAIL | Power Cycle | M-FT | L/XL | P/XP | XP-FT | GP/GX | S100/S300 | GroE | OCSM | OPzS | Energy Bloc/OGi | Solar | rail |
| Telecom | ● | ● | ● | ● | | | ● | ● | | ● | | | | | | | | | |
| UPS | ● | ● | ● | ● | | | ● | ● | ● | ● | | | | | | | | | |
| Emergency lighting | ● | ● | ● | ● | | | ● | ● | ● | ● | | | ● | | | | | | |
| Security | ● | | ● | ● | | | | | | ● | ● | | ● | | | | | | |
| Utility | ● | ● | | ● | | | ● | ● | | | | ● | | ● | ● | ● | ● | | |
| Railways | ● | ● | ● | ● | | ● | ● | ● | | | | ● | | | | | | | ● |
| Photovoltaic | | | | | ● | | ● | | | | | ● | | | | | | | ● |
| Universal | ● | ● | ● | ● | | | ● | ● | ● | ● | | ● | ● | | | | | | |

Powerful product brands

ABSOLYTE®

MARATHON®

Sprinter®

Powerfit®

- > VRLA batteries (Valve Regulated Lead Acid) in which the electrolyte is fixed in an Absorbent Glass Mat (AGM)
- > Excellent high current capability
- > Very economical
- > Maintenance-free (no topping up)



- > VRLA batteries (Valve Regulated Lead Acid) in which the electrolyte is fixed in a gel (dryfit® technology)
- > Inventor of Gel technology
- > Highest reliability, even in non-optimal conditions
- > Particularly suitable for cyclic applications
- > Maintenance-free (no topping up)

Classic®

- > Conventional lead-acid batteries with liquid electrolyte
- > Extreme reliability, proven over decades
- > Low maintenance

Sprinter P/XP

Maximized power density for highest requirements

The extremely powerful, compact AGM batteries of the Sprinter P and Sprinter XP series are an ideal energy source for uninterrupted power supply and are particularly good in UPS applications and other security systems. GNB's experience and innovation with VRLA technology makes Sprinter batteries the preferred choice for high rate emergency battery backup.

Your benefits:

- > **Excellent high current performance** – optimised for short discharge time
- > **Low self discharge rate** – extended storage capability
- > **Very short recharge time** – high availability
- > **Optimal power density** – saves floor space
- > **Completely recyclable** – low CO₂ footprint



Specifications:


- > Maintenance-free (no topping up) during the whole service life
 - > High-Compression Absorbent Glass Mat (AGM) technology
 - > Power (10 minutes) from 791 – 4500 watt
 - > Design life: »10-12 Years – Long Life« according to EURO-BAT 2015 classification
 - > Available as standard or flame retardant version (UL 94-V0)
 - > Designed in accordance with IEC 60896-21/-22
 - > Approval: UL (Underwriter Laboratories)
- > Grid plates with superior lead calcium alloy for excellent corrosion resistance
 - > Very low gassing due to internal gas recombination (99% efficiency)
 - > No restrictions for rail, road, sea and air transportation (IATA, DGR clause A67) – trouble-free transportation of operational blocks
 - > Manufactured in Europe in our ISO 9001 certified production plants




10-12 years
– Long Life



Nominal capacity
24.0 – 195 Ah



Block battery



Grid plate



Recyclable



Valve regulated
lead-acid
batteries



Maintenance
free (no
topping up)



Special high
current
performance

Sprinter P/XP

Technical data

Technical characteristics and data

| Type | Part number | Nom. voltage V | Power 10 min 1.60 Vpc 25°C W/block | Nominal capacity C ₁₀ 1.80 Vpc 25°C Ah | Nominal capacity C ₂₀ 1.75 Vpc 25°C Ah | Length (l) max. mm | Width (b/w) max. mm | Height (h1) max. mm | Height incl. connectors (h2) max. mm | Weight approx. kg | Internal resistance mOhm* | Short circuit current A* | Terminal |
|-----------------------|-----------------|-------------------|---|--|--|-----------------------|------------------------|------------------------|---|----------------------|------------------------------|-----------------------------|----------|
| P6V1700 | NAPW061700HP0MC | 6 | 2210 | 122 | 132 | 273 | 167 | 191 | 191 | 25.0 | 1.80 | 3416 | M-M8 |
| XP6V2800 | NAXP062800HP0FA | 6 | 2780 | 195 | 208 | 309 | 172 | 223 | 241 | 30.5 | 1.60 | 3828 | F-M6 |
| P12V600 | NAPW120600HP0MA | 12 | 791 | 24.0 | 26.0 | 169 | 128 | 175 | 175 | 9.50 | 15.4 | 824 | M-M6 |
| P12V875 | NAPW120875HP0MC | 12 | 1157 | 41.0 | 44.0 | 200 | 169 | 176 | 176 | 14.5 | 10.6 | 1178 | M-M6 |
| XP12V1800 | NAXP121800HP0FA | 12 | 1840 | 56.4 | 60.8 | 220 | 172 | 219 | 235 | 21.0 | 8.10 | 1558 | F-M6 |
| XP12V2500 | NAXP122500HP0FA | 12 | 2450 | 69.5 | 75.6 | 262 | 172 | 223 | 239 | 26.0 | 6.20 | 2046 | F-M6 |
| XP12V3000 | NAXP123000HP0FA | 12 | 3040 | 92.8 | 99.6 | 309 | 172 | 223 | 239 | 31.0 | 5.20 | 2425 | F-M6 |
| XP12V3400 | NAXP123400HP0FA | 12 | 3400 | 105 | 112 | 351 | 172 | 223 | 239 | 35.5 | 4.50 | 2767 | F-M6 |
| NEW! XP12V4400 | NAXP124400HP0FA | 12 | 4500 | 140 | 148 | 351 | 172 | 275 | 291 | 46.7 | 4.20 | 2961 | F-M6 |

* according IEC60896-21/22


P12V600, P12V875 and XP12V2500 with VdS approval

Container, terminal and torque


- > **Container:** - UL 94-HB = Polypropylene (PP)
- UL 94-V0 = Polypropylene (PP)

Figures are also valid for UL 94-V0 version.
Change »H« to »V« in the part number. E.g.:


- > **Standard:** NAXP122500 **H** P0FA
- > **UL 94-V0:** NAXP122500 **V** P0FA



6 Nm



8 Nm




11 Nm


Sprinter P/XP

Drawings


P6V1700




P12V875




P12V600




XP6V2800




XP12V1800




XP12V2500




XP12V3000



XP12V3400



XP12V4400



Not to scale!

Sprinter P/XP

Constant current discharge

1.90 Vpc – Discharge in A at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 286 | 285 | 286 | 267 | 223 | 187 | 162 | 125 | 94.0 | 76.1 | 41.4 | 29.2 | 19.1 | 12.7 | 10.9 |
| XP6V2800 | NAXP062800HPOFA | 290 | 290 | 290 | 270 | 238 | 238 | 200 | 160 | 127 | 107 | 67.0 | 48.8 | 32.5 | 21.4 | 17.4 |
| P12V600 | NAPW120600HPOMA | 78.0 | 75.0 | 70.0 | 62.0 | 47.0 | 37.0 | 30.0 | 22.0 | 17.0 | 13.4 | 8.00 | 5.90 | 4.00 | 2.60 | 2.10 |
| P12V875 | NAPW120875HPOMC | 96.0 | 96.0 | 96.0 | 85.0 | 65.0 | 52.0 | 44.0 | 35.0 | 26.0 | 21.1 | 12.8 | 9.40 | 6.30 | 4.30 | 3.70 |
| XP12V1800 | NAXP121800HPOFA | 152 | 152 | 152 | 152 | 113 | 89.5 | 72.7 | 54.3 | 39.8 | 33.5 | 19.2 | 13.8 | 9.40 | 6.00 | 5.10 |
| XP12V2500 | NAXP122500HPOFA | 173 | 173 | 173 | 173 | 134 | 115 | 95.5 | 73.0 | 54.6 | 43.4 | 23.0 | 15.8 | 10.7 | 7.18 | 6.04 |
| XP12V3000 | NAXP123000HPOFA | 195 | 195 | 195 | 195 | 195 | 140 | 120 | 94.2 | 70.0 | 56.7 | 33.5 | 24.8 | 15.7 | 10.1 | 8.21 |
| XP12V3400 | NAXP123400HPOFA | 200 | 200 | 200 | 200 | 195 | 140 | 122 | 97.0 | 76.0 | 62.0 | 37.6 | 26.7 | 16.5 | 10.7 | 8.70 |
| XP12V4400 | NAXP124400HPOFA | 250 | 250 | 250 | 250 | 217 | 192 | 167 | 129 | 98 | 78.3 | 49.4 | 35.5 | 22.4 | 14.6 | 11.8 |

1.85 Vpc – Discharge in A at 25 °C

| Type | Part number | 1min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 390 | 385 | 388 | 349 | 279 | 227 | 192 | 145 | 107 | 83.4 | 46.3 | 32.5 | 21.3 | 13.8 | 11.6 |
| XP6V2800 | NAXP062800HPOFA | 473 | 473 | 473 | 473 | 399 | 320 | 270 | 201 | 151 | 123 | 73.9 | 54.0 | 35.4 | 23.1 | 18.8 |
| P12V600 | NAPW120600HPOMA | 98.0 | 93.0 | 87.0 | 76.0 | 55.0 | 43.0 | 35.0 | 25.0 | 19.0 | 15.2 | 9.20 | 6.70 | 4.40 | 2.80 | 2.30 |
| P12V875 | NAPW120875HPOMC | 128 | 128 | 128 | 109 | 79.0 | 62.0 | 52.0 | 40.0 | 29.0 | 24.0 | 14.4 | 10.6 | 7.00 | 4.70 | 3.90 |
| XP12V1800 | NAXP121800HPOFA | 189 | 189 | 189 | 189 | 134 | 104 | 83.4 | 61.4 | 44.5 | 37.3 | 21.7 | 15.5 | 10.2 | 6.40 | 5.40 |
| XP12V2500 | NAXP122500HPOFA | 218 | 218 | 218 | 218 | 158 | 130 | 109 | 82.1 | 60.8 | 47.9 | 25.0 | 17.3 | 11.5 | 7.70 | 6.67 |
| XP12V3000 | NAXP123000HPOFA | 225 | 225 | 225 | 220 | 209 | 165 | 140 | 107 | 78.8 | 63.1 | 36.3 | 26.6 | 16.9 | 11.0 | 8.94 |
| XP12V3400 | NAXP123400HPOFA | 270 | 270 | 270 | 270 | 213 | 176 | 150 | 115 | 85.0 | 68.0 | 40.6 | 28.9 | 18.3 | 11.8 | 9.60 |
| XP12V4400 | NAXP124400HPOFA | 291 | 291 | 291 | 291 | 261 | 226 | 200 | 154 | 117 | 91 | 53.7 | 38.3 | 24.1 | 15.7 | 12.7 |

1.80 Vpc – Discharge in A at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 503 | 489 | 479 | 421 | 319 | 254 | 209 | 155 | 114 | 89.4 | 49.3 | 34.3 | 22.8 | 14.7 | 12.2 |
| XP6V2800 | NAXP062800HPOFA | 510 | 505 | 497 | 497 | 440 | 360 | 300 | 222 | 164 | 132 | 77.3 | 56.0 | 36.4 | 23.6 | 19.5 |
| P12V600 | NAPW120600HPOMA | 112 | 109 | 107 | 87.0 | 61.0 | 46.0 | 38.0 | 27.0 | 20.0 | 16.2 | 9.70 | 7.10 | 4.60 | 2.90 | 2.40 |
| P12V875 | NAPW120875HPOMC | 160 | 156 | 153 | 127 | 89.0 | 68.0 | 56.0 | 42.0 | 31.0 | 25.4 | 15.4 | 11.4 | 7.50 | 4.90 | 4.10 |
| XP12V1800 | NAXP121800HPOFA | 221 | 207 | 213 | 213 | 147 | 113 | 90.3 | 66.1 | 48.0 | 39.8 | 22.6 | 16.3 | 10.6 | 6.83 | 5.64 |
| XP12V2500 | NAXP122500HPOFA | 276 | 259 | 254 | 254 | 180 | 144 | 117 | 87.6 | 65.8 | 51.6 | 27.6 | 18.8 | 12.1 | 8.00 | 6.95 |
| XP12V3000 | NAXP123000HPOFA | 331 | 310 | 271 | 271 | 229 | 182 | 153 | 115 | 84.1 | 66.9 | 37.8 | 27.4 | 17.5 | 11.4 | 9.28 |
| XP12V3400 | NAXP123400HPOFA | 378 | 357 | 340 | 315 | 240 | 195 | 164 | 125 | 93.0 | 74.0 | 43.0 | 30.3 | 19.5 | 12.8 | 10.5 |
| XP12V4400 | NAXP124400HPOFA | 455 | 436 | 418 | 373 | 323 | 264 | 233 | 180 | 135 | 107 | 59.9 | 42.5 | 26.7 | 17.3 | 14 |

1.75 Vpc – Discharge in A at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 590 | 573 | 562 | 483 | 353 | 275 | 223 | 163 | 117 | 92.4 | 51.4 | 35.3 | 23.5 | 15.2 | 12.5 |
| XP6V2800 | NAXP062800HPOFA | 580 | 575 | 568 | 568 | 468 | 385 | 320 | 236 | 172 | 138 | 78.6 | 57.0 | 37.0 | 24.0 | 19.9 |
| P12V600 | NAPW120600HPOMA | 123 | 120 | 118 | 95.0 | 65.0 | 49.0 | 40.0 | 28.0 | 20.8 | 17.1 | 9.90 | 7.30 | 4.70 | 3.00 | 2.50 |
| P12V875 | NAPW120875HPOMC | 176 | 171 | 168 | 138 | 95.0 | 72.0 | 59.0 | 44.0 | 33.0 | 26.6 | 16.2 | 11.8 | 7.70 | 5.10 | 4.30 |
| XP12V1800 | NAXP121800HPOFA | 260 | 243 | 235 | 235 | 158 | 121 | 96.3 | 69.6 | 49.3 | 41.6 | 23.4 | 16.9 | 11.0 | 6.94 | 5.75 |
| XP12V2500 | NAXP122500HPOFA | 347 | 317 | 282 | 282 | 194 | 154 | 125 | 92.5 | 68.0 | 53.2 | 28.5 | 19.5 | 12.4 | 8.20 | 7.07 |
| XP12V3000 | NAXP123000HPOFA | 417 | 382 | 307 | 307 | 240 | 192 | 160 | 120 | 87.0 | 68.9 | 38.6 | 27.8 | 17.8 | 11.5 | 9.41 |
| XP12V3400 | NAXP123400HPOFA | 465 | 426 | 410 | 357 | 271 | 218 | 181 | 135 | 98.0 | 77.0 | 44.2 | 30.9 | 20.0 | 13.0 | 10.7 |
| XP12V4400 | NAXP124400HPOFA | 543 | 501 | 469 | 423 | 359 | 290 | 252 | 188 | 139 | 111 | 62.4 | 43.7 | 27.6 | 17.7 | 14.3 |

Sprinter P/XP

Constant current discharge

1.70 Vpc – Discharge in A at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HP0MC | 755 | 692 | 629 | 529 | 377 | 291 | 234 | 168 | 120 | 94.5 | 53.3 | 36.5 | 24.2 | 15.4 | 12.6 |
| XP6V2800 | NAXP062800HP0FA | 760 | 700 | 643 | 643 | 494 | 400 | 330 | 243 | 177 | 141 | 80.0 | 58.0 | 37.6 | 24.4 | 20.0 |
| P12V600 | NAPW120600HP0MA | 154 | 141 | 129 | 103 | 69.0 | 52.0 | 42.0 | 29.4 | 21.8 | 17.6 | 10.3 | 7.40 | 4.80 | 3.10 | 2.60 |
| P12V875 | NAPW120875HP0MC | 220 | 202 | 184 | 148 | 99.0 | 75.0 | 61.0 | 45.2 | 34.0 | 27.6 | 16.8 | 12.2 | 7.90 | 5.20 | 4.40 |
| XP12V1800 | NAXP121800HP0FA | 301 | 269 | 254 | 254 | 168 | 127 | 100 | 71.9 | 51.1 | 42.9 | 24.0 | 17.2 | 11.2 | 7.05 | 5.86 |
| XP12V2500 | NAXP122500HP0FA | 382 | 347 | 308 | 308 | 205 | 160 | 130 | 95.4 | 69.3 | 54.3 | 29.0 | 20.0 | 12.7 | 8.30 | 7.14 |
| XP12V3000 | NAXP123000HP0FA | 459 | 413 | 342 | 340 | 250 | 200 | 164 | 122 | 88.5 | 70.1 | 39.1 | 28.1 | 17.9 | 11.6 | 9.49 |
| XP12V3400 | NAXP123400HP0FA | 535 | 485 | 470 | 400 | 293 | 229 | 188 | 139 | 100 | 78.5 | 44.8 | 31.5 | 20.2 | 13.2 | 10.8 |
| XP12V4400 | NAXP124400HP0FA | 625 | 566 | 521 | 461 | 387 | 300 | 258 | 190 | 141 | 112 | 63 | 44.1 | 27.8 | 18 | 14.5 |

1.65 Vpc – Discharge in A at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HP0MC | 811 | 740 | 676 | 563 | 395 | 299 | 241 | 173 | 123 | 96.5 | 54.6 | 37.8 | 24.3 | 15.5 | 12.6 |
| XP6V2800 | NAXP062800HP0FA | 820 | 750 | 717 | 717 | 521 | 418 | 340 | 247 | 179 | 143 | 80.8 | 58.6 | 38.1 | 24.8 | 20.1 |
| P12V600 | NAPW120600HP0MA | 163 | 149 | 135 | 109 | 71.0 | 54.0 | 43.0 | 30.5 | 22.3 | 18.0 | 10.4 | 7.50 | 4.80 | 3.10 | 2.60 |
| P12V875 | NAPW120875HP0MC | 237 | 217 | 198 | 157 | 104 | 77.0 | 63.0 | 46.2 | 35.0 | 28.4 | 17.5 | 12.5 | 8.00 | 5.30 | 4.40 |
| XP12V1800 | NAXP121800HP0FA | 341 | 309 | 266 | 266 | 173 | 129 | 101 | 73.1 | 52.4 | 43.7 | 24.3 | 17.4 | 11.3 | 7.10 | 5.86 |
| XP12V2500 | NAXP122500HP0FA | 418 | 381 | 325 | 325 | 211 | 164 | 133 | 97.0 | 70.5 | 55.2 | 29.5 | 20.3 | 12.8 | 8.40 | 7.18 |
| XP12V3000 | NAXP123000HP0FA | 512 | 463 | 373 | 366 | 260 | 205 | 167 | 124 | 89.6 | 70.8 | 39.4 | 28.3 | 18.0 | 11.7 | 9.56 |
| XP12V3400 | NAXP123400HP0FA | 598 | 540 | 540 | 440 | 306 | 237 | 193 | 142 | 102 | 80.0 | 45.3 | 32.0 | 20.4 | 13.4 | 10.9 |
| XP12V4400 | NAXP124400HP0FA | 667 | 611 | 565 | 500 | 403 | 315 | 264 | 196 | 148 | 117 | 65.1 | 45.7 | 28.8 | 18.6 | 15.1 |

1.60 Vpc – Discharge in A at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|------|------|------|------|------|
| P6V1700 | NAPW061700HP0MC | 838 | 760 | 698 | 582 | 406 | 308 | 247 | 177 | 126 | 98.5 | 55.4 | 38.4 | 24.4 | 15.5 | 12.6 |
| XP6V2800 | NAXP062800HP0FA | 840 | 810 | 791 | 791 | 546 | 430 | 348 | 250 | 181 | 144 | 81.7 | 59.2 | 38.5 | 24.9 | 20.2 |
| P12V600 | NAPW120600HP0MA | 171 | 157 | 140 | 113 | 73.0 | 55.0 | 44.0 | 31.0 | 22.8 | 18.3 | 10.5 | 7.60 | 4.80 | 3.10 | 2.60 |
| P12V875 | NAPW120875HP0MC | 250 | 229 | 209 | 164 | 107 | 79.0 | 65.0 | 47.2 | 36.0 | 29.2 | 17.9 | 12.6 | 8.00 | 5.30 | 4.40 |
| XP12V1800 | NAXP121800HP0FA | 363 | 327 | 276 | 276 | 176 | 131 | 103 | 74.2 | 52.9 | 44.1 | 24.5 | 17.6 | 11.3 | 7.10 | 5.86 |
| XP12V2500 | NAXP122500HP0FA | 454 | 409 | 338 | 338 | 218 | 168 | 135 | 98.8 | 71.9 | 56.1 | 30.0 | 20.6 | 12.9 | 8.50 | 7.20 |
| XP12V3000 | NAXP123000HP0FA | 545 | 490 | 399 | 385 | 268 | 210 | 171 | 126 | 90.5 | 71.5 | 39.7 | 28.5 | 18.2 | 11.8 | 9.61 |
| XP12V3400 | NAXP123400HP0FA | 636 | 620 | 610 | 490 | 323 | 245 | 196 | 145 | 105 | 82.0 | 45.8 | 32.3 | 20.6 | 13.5 | 11.0 |
| XP12V4400 | NAXP124400HP0FA | 713 | 648 | 602 | 532 | 417 | 324 | 269 | 200 | 150 | 118 | 65.7 | 46.2 | 29.2 | 18.9 | 15.3 |



Sprinter P/XP

Constant power discharge

1.90 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|-----|------|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 1641 | 1641 | 1641 | 1537 | 1267 | 1067 | 919 | 711 | 545 | 445 | 246 | 174 | 114 | 76.1 | 62.9 |
| XP6V2800 | NAXP062800HP0FA | 1400 | 1400 | 1400 | 1400 | 1400 | 1400 | 1210 | 1010 | 785 | 659 | 410 | 298 | 192 | 127 | 104 |
| P12V600 | NAPW120600HPOMA | 834 | 834 | 834 | 725 | 539 | 427 | 356 | 271 | 200 | 162 | 97.4 | 71.1 | 47.7 | 31.5 | 26.4 |
| P12V875 | NAPW120875HPOMC | 1151 | 1151 | 1151 | 1006 | 762 | 608 | 506 | 397 | 304 | 253 | 153 | 112 | 76.1 | 50.8 | 43.6 |
| XP12V1800 | NAXP121800HP0FA | 1760 | 1760 | 1760 | 1759 | 1249 | 982 | 840 | 670 | 496 | 387 | 226 | 160 | 103 | 72.1 | 59.5 |
| XP12V2500 | NAXP122500HP0FA | 2000 | 2000 | 2000 | 2000 | 1590 | 1309 | 1108 | 853 | 598 | 508 | 283 | 199 | 127 | 85.3 | 69.6 |
| XP12V3000 | NAXP123000HP0FA | 2250 | 2250 | 2250 | 2250 | 2000 | 1700 | 1400 | 1120 | 841 | 682 | 405 | 301 | 193 | 124 | 100 |
| XP12V3400 | NAXP123400HP0FA | 2600 | 2600 | 2600 | 2600 | 2100 | 1756 | 1504 | 1180 | 895 | 726 | 457 | 328 | 208 | 135 | 109 |
| XP12V4400 | NAXP124400HP0FA | 3000 | 3000 | 3000 | 3000 | 2600 | 2300 | 2000 | 1553 | 1178 | 956 | 603 | 433 | 274 | 178 | 143 |

1.85 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|-----|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 2176 | 2176 | 2176 | 1982 | 1586 | 1302 | 1107 | 848 | 632 | 498 | 279 | 193 | 126 | 82.2 | 68.0 |
| XP6V2800 | NAXP062800HP0FA | 2230 | 2230 | 2230 | 2230 | 2000 | 1730 | 1500 | 1160 | 875 | 718 | 436 | 314 | 201 | 132 | 107 |
| P12V600 | NAPW120600HPOMA | 1033 | 1033 | 1033 | 868 | 627 | 491 | 406 | 300 | 221 | 179 | 108 | 79.2 | 51.8 | 33.5 | 28.4 |
| P12V875 | NAPW120875HPOMC | 1441 | 1441 | 1441 | 1225 | 906 | 718 | 597 | 462 | 352 | 284 | 170 | 126 | 84.2 | 54.8 | 46.7 |
| XP12V1800 | NAXP121800HP0FA | 2110 | 2110 | 2110 | 2110 | 1450 | 1120 | 952 | 745 | 547 | 430 | 253 | 181 | 112 | 77.7 | 64.0 |
| XP12V2500 | NAXP122500HP0FA | 2300 | 2300 | 2300 | 2300 | 1830 | 1519 | 1261 | 949 | 658 | 568 | 307 | 217 | 138 | 91.9 | 74.8 |
| XP12V3000 | NAXP123000HP0FA | 2830 | 2830 | 2830 | 2830 | 2200 | 2050 | 1600 | 1260 | 928 | 747 | 433 | 319 | 205 | 133 | 108 |
| XP12V3400 | NAXP123400HP0FA | 3046 | 3046 | 3046 | 3046 | 2472 | 2074 | 1783 | 1399 | 1054 | 853 | 490 | 349 | 220 | 142 | 115 |
| XP12V4400 | NAXP124400HP0FA | 3351 | 3351 | 3351 | 3351 | 3000 | 2600 | 2300 | 1775 | 1346 | 1092 | 645 | 459 | 290 | 188 | 153 |

1.80 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|-----|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 2897 | 2765 | 2634 | 2349 | 1808 | 1454 | 1212 | 906 | 664 | 523 | 290 | 203 | 136 | 88.3 | 72.6 |
| XP6V2800 | NAXP062800HP0FA | 3250 | 3000 | 2750 | 2500 | 2320 | 1950 | 1650 | 1250 | 925 | 758 | 448 | 325 | 208 | 136 | 111 |
| P12V600 | NAPW120600HPOMA | 1250 | 1210 | 1171 | 971 | 689 | 532 | 435 | 320 | 235 | 192 | 113 | 82.2 | 54.8 | 35.5 | 29.4 |
| P12V875 | NAPW120875HPOMC | 2000 | 1820 | 1688 | 1418 | 1013 | 785 | 650 | 492 | 372 | 301 | 183 | 135 | 89.3 | 57.9 | 48.2 |
| XP12V1800 | NAXP121800HP0FA | 2600 | 2440 | 2280 | 2359 | 1590 | 1219 | 1020 | 793 | 583 | 459 | 262 | 190 | 121 | 82.1 | 66.1 |
| XP12V2500 | NAXP122500HP0FA | 3250 | 3050 | 2850 | 2650 | 2020 | 1650 | 1350 | 1000 | 700 | 604 | 325 | 234 | 145 | 96.3 | 78.1 |
| XP12V3000 | NAXP123000HP0FA | 3900 | 3650 | 3420 | 3180 | 2400 | 2100 | 1750 | 1320 | 982 | 786 | 450 | 328 | 210 | 136 | 111 |
| XP12V3400 | NAXP123400HP0FA | 4450 | 4200 | 3990 | 3499 | 2719 | 2250 | 1927 | 1500 | 1126 | 904 | 505 | 358 | 225 | 145 | 118 |
| XP12V4400 | NAXP124400HP0FA | 5000 | 4800 | 4600 | 4100 | 3550 | 2900 | 2560 | 1974 | 1482 | 1191 | 665 | 471 | 296 | 192 | 155 |

1.75 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|-----|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 3290 | 3172 | 3021 | 2654 | 1982 | 1566 | 1282 | 950 | 689 | 541 | 300 | 211 | 140 | 89.3 | 73.6 |
| XP6V2800 | NAXP062800HP0FA | 3750 | 3500 | 3250 | 3000 | 2440 | 2060 | 1750 | 1310 | 965 | 775 | 455 | 332 | 212 | 138 | 113 |
| P12V600 | NAPW120600HPOMA | 1400 | 1350 | 1266 | 1045 | 732 | 565 | 458 | 336 | 246 | 203 | 116 | 85.3 | 55.8 | 36.5 | 29.9 |
| P12V875 | NAPW120875HPOMC | 2200 | 2000 | 1823 | 1523 | 1074 | 827 | 680 | 513 | 386 | 315 | 192 | 140 | 91.4 | 58.9 | 49.2 |
| XP12V1800 | NAXP121800HP0FA | 3000 | 2800 | 2600 | 2539 | 1699 | 1290 | 1080 | 832 | 607 | 478 | 271 | 196 | 124 | 83.2 | 67.3 |
| XP12V2500 | NAXP122500HP0FA | 4000 | 3650 | 3350 | 3080 | 2220 | 1759 | 1438 | 1060 | 727 | 631 | 337 | 244 | 148 | 97.5 | 79.0 |
| XP12V3000 | NAXP123000HP0FA | 4800 | 4400 | 4100 | 3499 | 2680 | 2260 | 1855 | 1390 | 1009 | 807 | 457 | 331 | 211 | 138 | 112 |
| XP12V3400 | NAXP123400HP0FA | 5350 | 4900 | 4494 | 3897 | 2976 | 2434 | 2052 | 1567 | 1162 | 931 | 525 | 367 | 232 | 148 | 120 |
| XP12V4400 | NAXP124400HP0FA | 5900 | 5450 | 5100 | 4600 | 3900 | 3150 | 2740 | 2064 | 1531 | 1227 | 691 | 484 | 305 | 196 | 158 |

Sprinter P/XP

Constant power discharge

1.70 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|-----|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 3498 | 3339 | 3180 | 2876 | 2092 | 1628 | 1331 | 977 | 699 | 552 | 311 | 218 | 142 | 90.3 | 74.1 |
| XP6V2800 | NAXP062800HP0FA | 4000 | 3750 | 3500 | 3250 | 2560 | 2140 | 1790 | 1340 | 980 | 789 | 463 | 338 | 216 | 140 | 114 |
| P12V600 | NAPW120600HPOMA | 1600 | 1460 | 1348 | 1101 | 762 | 579 | 469 | 343 | 251 | 205 | 118 | 87.3 | 56.8 | 37.0 | 30.5 |
| P12V875 | NAPW120875HPOMC | 2400 | 2150 | 1948 | 1605 | 1109 | 843 | 694 | 525 | 398 | 327 | 197 | 145 | 93.4 | 59.9 | 50.2 |
| XP12V1800 | NAXP121800HP0FA | 3470 | 3100 | 2840 | 2680 | 1760 | 1330 | 1110 | 855 | 622 | 488 | 276 | 199 | 129 | 84.3 | 68.4 |
| XP12V2500 | NAXP122500HP0FA | 4400 | 4000 | 3650 | 3330 | 2330 | 1820 | 1476 | 1080 | 739 | 641 | 346 | 249 | 150 | 98.3 | 79.2 |
| XP12V3000 | NAXP123000HP0FA | 5280 | 4750 | 4330 | 3780 | 2790 | 2310 | 1897 | 1420 | 1020 | 818 | 462 | 334 | 214 | 139 | 114 |
| XP12V3400 | NAXP123400HP0FA | 6160 | 5580 | 5050 | 4276 | 3146 | 2515 | 2100 | 1590 | 1180 | 945 | 530 | 371 | 234 | 151 | 122 |
| XP12V4400 | NAXP124400HP0FA | 6776 | 6138 | 5650 | 5000 | 4200 | 3250 | 2800 | 2093 | 1553 | 1244 | 698 | 488 | 308 | 199 | 161 |

1.65 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|-----|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 3873 | 3697 | 3521 | 3008 | 2160 | 1662 | 1358 | 993 | 713 | 560 | 316 | 222 | 143 | 91.4 | 74.1 |
| XP6V2800 | NAXP062800HP0FA | 4250 | 4000 | 3750 | 3500 | 2679 | 2200 | 1820 | 1360 | 999 | 806 | 469 | 343 | 220 | 143 | 116 |
| P12V600 | NAPW120600HPOMA | 1700 | 1550 | 1422 | 1150 | 781 | 592 | 477 | 346 | 256 | 207 | 120 | 88.0 | 57.0 | 37.0 | 31.0 |
| P12V875 | NAPW120875HPOMC | 2590 | 2300 | 2068 | 1677 | 1133 | 858 | 706 | 533 | 405 | 332 | 202 | 148 | 94.4 | 60.9 | 50.8 |
| XP12V1800 | NAXP121800HP0FA | 3760 | 3400 | 3084 | 2790 | 1810 | 1350 | 1120 | 868 | 628 | 496 | 279 | 202 | 130 | 84.3 | 68.4 |
| XP12V2500 | NAXP122500HP0FA | 4600 | 4200 | 3855 | 3440 | 2400 | 1849 | 1501 | 1099 | 751 | 645 | 348 | 250 | 151 | 98.8 | 80.2 |
| XP12V3000 | NAXP123000HP0FA | 5640 | 5100 | 4626 | 4009 | 2869 | 2330 | 1909 | 1430 | 1030 | 825 | 465 | 336 | 216 | 139 | 114 |
| XP12V3400 | NAXP123400HP0FA | 6580 | 5950 | 5397 | 4584 | 3300 | 2595 | 2149 | 1620 | 1201 | 960 | 535 | 376 | 237 | 153 | 124 |
| XP12V4400 | NAXP124400HP0FA | 7200 | 6600 | 6100 | 5400 | 4350 | 3400 | 2850 | 2150 | 1622 | 1296 | 722 | 508 | 320 | 207 | 167 |

1.60 Vpc – Discharge in W/block at 25 °C

| Type | Part number | 1 min | 2 min | 3 min | 5 min | 10 min | 15 min | 20 min | 30 min | 45 min | 1 h | 2 h | 3 h | 5 h | 8 h | 10 h |
|-----------|-----------------|-------|-------|-------|-------|--------|--------|--------|--------|--------|------|-----|------|------|------|------|
| P6V1700 | NAPW061700HPOMC | 3956 | 3776 | 3597 | 3063 | 2210 | 1700 | 1379 | 1002 | 720 | 567 | 319 | 224 | 143 | 91.4 | 74.1 |
| XP6V2800 | NAXP062800HP0FA | 4500 | 4250 | 4000 | 3750 | 2780 | 2250 | 1850 | 1380 | 1010 | 819 | 474 | 348 | 222 | 144 | 117 |
| P12V600 | NAPW120600HPOMA | 1800 | 1620 | 1477 | 1186 | 792 | 600 | 480 | 349 | 259 | 208 | 121 | 88.0 | 57.0 | 37.0 | 31.0 |
| P12V875 | NAPW120875HPOMC | 2700 | 2400 | 2155 | 1730 | 1156 | 874 | 718 | 541 | 409 | 337 | 204 | 148 | 94.4 | 60.9 | 50.8 |
| XP12V1800 | NAXP121800HP0FA | 4000 | 3600 | 3280 | 2869 | 1840 | 1369 | 1140 | 877 | 637 | 502 | 283 | 202 | 130 | 84.3 | 68.4 |
| XP12V2500 | NAXP122500HP0FA | 5000 | 4500 | 4100 | 3580 | 2449 | 1870 | 1516 | 1110 | 754 | 648 | 349 | 253 | 153 | 99.4 | 80.2 |
| XP12V3000 | NAXP123000HP0FA | 6000 | 5400 | 4920 | 4180 | 3040 | 2350 | 1914 | 1440 | 1039 | 829 | 466 | 337 | 217 | 141 | 115 |
| XP12V3400 | NAXP123400HP0FA | 7000 | 6300 | 5740 | 4849 | 3400 | 2640 | 2185 | 1645 | 1219 | 970 | 540 | 379 | 240 | 154 | 126 |
| XP12V4400 | NAXP124400HP0FA | 7700 | 7000 | 6500 | 5750 | 4500 | 3500 | 2900 | 2200 | 1647 | 1310 | 729 | 513 | 324 | 209 | 170 |



Battery Service – Energy Solutions

Keeping your business on the move

GNB® is the Expert


Who could do this job better than the professionals of a company with more than 100 years of experience in battery development, production and application?

Leave the responsibility for the maintenance of your batteries and chargers to the professionals: a GNB service contract provides you with exceptional economic advantages through time savings, cost savings and safety!



Installation of Batteries and Systems for Network Power

- > Development of complete turnkey solutions from the design concept to installation and commissioning.
- > Installation according to legal and safety regulations including CE certification by approved installation technicians.
- > Training and certification of external installation technicians according to CE regulations.



- ✦ Inspection Contract
- ✦ Maintenance Contract
- ✦ Lifetime Warranty Contract
- ✦ Full Service Contract



»GNB Service – individualized, professional and all over Europe!«



Exide Technologies, with operations in more than 80 countries, is one of the world's largest producers and recyclers of lead-acid batteries. Exide Technologies provides a comprehensive and customized range of stored electrical energy solutions. Based on over 120 years of experience in the development of innovative technologies, Exide Technologies is an esteemed partner of OEMs and serves the spare parts market for industrial and automotive applications.

GNB Industrial Power – A division of Exide Technologies – offers an extensive range of storage products and services, including solutions for telecommunication systems, railway applications, mining, photovoltaic (solar energy), uninterrupted power supply (UPS), electrical power generation and distribution, fork lifts and electric vehicles.

Exide Technologies takes pride in its commitment to a better environment. An integrated approach to manufacturing, distributing and recycling of lead-acid batteries has been developed to ensure a safe and responsible life cycle for all of its products.

GNB[®] INDUSTRIAL POWER devises enduring energy concepts that convince with efficiency, flexibility and profitability.